

Part Number/Price (Limited Supply)

Part #	Description	Est. Weight	Price
68539	Allen-Bradley remote I/O (internal), for 720i/920i indicators	3 lb	Consult

Options/Accessories

Part #	Description	Price
69950	Additional operating manual	Consult

FIELDBUS CARDS Remote I/O Interface 720j[™]/920j[®]

Standard Features

- 115 or 230 VAC operation
- Discrete data transfer
- Block data transfer
- Onboard diagnostic LED

Specifications

Power:

5 VDC, 140 mA

- Communication Ports: Twin axial cable attachment to network at 57.6, 115.2 or 230.4 Kbps Update rate is dependent on the configured baud rate and the number of network modes
- Fieldbus Interface:
- Pluggable screw connector
- Diagnostic LED:
- Network status
- Dimensions: 2.13 × 3.38 × 0.59 in (86 × 54 × 15 mm)
- Temperature Range:
- 14 °F to 158 °F (-10 °C to 70 °C)

FIELDBUS CARDS DeviceNet[™] Interface

720i[™]/920i®



Part Number/Price

69949 Additional operating manual

Part #	Description	Est. Weight	Price				
68541	DeviceNet interface kit for 720i/920i indicators	3 lb	Consult				
Options/Accessories							
Part #	Description		Price				

Standard Features

- DeviceNet communication adapter
- Compact size for internal installation in 720 and 920i indicators
- Polled I/O connection
- 125 Kbps, 250 Kbps, and 500 Kbps baud rate
- Onboard LED diagnostics
- Floating-point commands support decimal points

Specifications

Power:

5 VDC, 270 mA Fieldbus connector requires 24 VDC, ±10%

Communication Ports:

Twisted-pair cabling at 125, 250, or 500 Kbps Update rate is dependent on the configured baud rate and the number of network modes

Fieldbus Interface:

Pluggable screw connector

Diagnostic LEDs:

Network status, module status

Dimensions:

2.13 × 3.38 × 0.59 in (86 × 54 × 15 mm)

Temperature Range:

14 °F to 158 °F (-10 °C to 70 °C)

Galvanic Isolation:

Bus power is separated from other electronics via DC/DC converter. The send and receive signals are isolated via opto couplers.

Consult

